

Brush Buster BT



Photo may contain optional equipment

Brush Buster BT

Steel gooseneck bar top stock trailer with high brush fenders

Standard Features

Available sizes

Gooseneck, 12' floor length, 5' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 14' floor length, 5' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 5' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 5' width w/2-5200# axles, 16" tires & 6-hole wheels
Gooseneck, 16' floor length, 5' width w/2-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 12' floor length, 6' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 14' floor length, 6' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 6' width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 6' width w/2-5200# axles, 16" tires & 6-hole wheels
Gooseneck, 16' floor length, 6' width w/2-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 20' floor length, 6' width w/2-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 20' floor length, 6' width w/2-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 24' floor length, 6' width w/2-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 24' floor length, 6' width w/2-8000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6' width w/3-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6' width w/3-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6' width w/2-8000# axles, 16" tires & 8-hole wheels
Gooseneck, 32' floor length, 6' width w/3-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 12' floor length, 6'-8" width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 14' floor length, 6'-8" width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 6'-8" width w/2-5200# axles, 15" tires & 6-hole wheels
Gooseneck, 16' floor length, 6'-8" width w/2-5200# axles, 16" tires & 6-hole wheels
Gooseneck, 16' floor length, 6'-8" width w/2-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 20' floor length, 6'-8" width w/2-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 20' floor length, 6'-8" width w/2-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 24' floor length, 6'-8" width w/2-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 24' floor length, 6'-8" width w/2-8000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6'-8" width w/3-6000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6'-8" width w/3-7000# axles, 16" tires & 8-hole wheels
Gooseneck, 28' floor length, 6'-8" width w/2-8000# axles, 16" tires & 8-hole wheels
Gooseneck, 32' floor length, 6'-8" width w/3-7000# axles, 16" tires & 8-hole wheels

Dimensions

6'-6" body height
5', 6' or 6'-8" body width (6'8" wide has no wheel well, 102" overall)
(14' x 6' wide models have w/2-5200# axles, 6-hole 15" tires and wheels)
7' gooseneck length

Undercarriage

Rubber torsion axles with four wheel independent suspension and greasable hubs for easy lubrication
Electric brakes on all wheels
Radial tires on silver modular wheels with chrome center caps
Spare tire, wheel and rack

Coupler & Jacks

Adjustable hitch stem with 2-5/16" coupler and safety chains with hooks
Heavy duty low profile gooseneck structure
Single speed drop-leg jack
Emergency breakaway system: switch, cable and battery box complete with battery (less charger)

Design Features & Hardware

All steel frame with formed high fenders
Pipe over construction with 1" x 3" tubing sides
High brush fenders full trailer length
Half open front under gooseneck
Treated floor
Greasable exterior hinges
Pin striping (upper and lower region only)
Tag bracket

Load Area Equipment

One center gate - 24' lengths and above have two gates and the 32' has three gate
(no center gate on 12' models)
Double swing in and out butterfly rear gates

Lights

DOT required lighting (stop, turn, tail, tag, marker, clearance & conspicuity tape)