

Cargo Mite



Photo may contain optional equipment

Cargo Mite

Steel bumper pull cargo trailer single axle with brakes (also available without brakes)

Standard Features

Available sizes

Bumper pull, 08' x 5' width, w/1-3500# axle, 5-hole 15" tires and wheels
Bumper pull, 08' x 5' width, w/1-2900# axle, 5-hole 15" tires and wheels
Bumper pull, 10' x 5' width, w/1-3500# axle, 5-hole 15" tires and wheels
Bumper pull, 10' x 5' width, w/1-2900# axle, 5-hole 15" tires and wheels
Bumper pull, 10' x 6' width, w/1-3500# axle, 5-hole 15" tires and wheels
Bumper pull, 10' x 6' width, w/1-2900# axle, 5-hole 15" tires and wheels
Bumper pull, 12' x 6' width, w/1-3500# axle, 5-hole 15" tires and wheels
Bumper pull, 12' x 6' width, w/1-2900# axle, 5-hole 15" tires and wheels

Dimensions

5' body height (5' wide models only) or 5'-6" body height (6' wide models only)
5' body width (5' height models only) or 6' body width (5'-6" height models only)
36" tongue length

Undercarriage

Rubber torsion axles with all wheel independent suspension and greasable hubs for easy lubrication
Electric brakes on all wheels (2900# model without brakes and 3500# model with electric brakes)
Silver modular wheels with chrome center caps

Coupler & Jacks

2" coupler with safety chains and hooks
Top-wind screw jack with sand plate
Emergency breakaway system: switch, cable and battery box complete with battery (less charger)

Design Features & Hardware

Low profile 6" radius corner galvanized roof
All steel tubular frame with smooth galvanized side panels

3/4" exterior plywood floor
Aluminum tread plate gravel guard
Steel hold backs on all full height doors
Chrome trim with colored vinyl insert
Paint color and code #GMA79:12 White
Pin striping (upper and lower region only)
Tag bracket

Cargo Area Equipment

One-piece rear door with cam latch and hold back
Inside tie rail standard on 6' wide only

Lights

DOT required lighting (stop, turn, tail, tag, marker & clearance)