

Stocker



Photo may contain optional equipment

Stocker

Steel bumper pull stock trailer

Standard Features

Available sizes

Bumper pull, 10' floor length w/2-3500# axles, 15" tires & 5-hole wheels
 Bumper pull, 12' floor length w/2-3500# axles, 15" tires & 5-hole wheels
 Bumper pull, 14' floor length w/2-3500# axles, 15" tires & 5-hole wheels
 Bumper pull, 16' floor length w/2-5200# axles, 15" tires & 6-hole wheels
 Bumper pull, 17' floor length w/2-5200# axles, 15" tires & 6-hole wheels

Dimensions

6' body height
 5' or 6' body width (17' available only in 6' width)
 (14' x 6' wide models have w/2-5200# axles, 6-hole 15" tires and wheels)
 28" tongue length

Undercarriage

Rubber torsion axles with four wheel independent suspension and greasable hubs for easy lubrication
 Electric brakes on all wheels
 Radial tires on silver modular wheels with chrome center caps
 Spare tire rack only

Coupler & Jacks

2" coupler and safety chains with hooks (standard on 5' widths 10'-14' and 6' widths 10'-12')
 2-5/16" coupler and safety chains with hooks (standard on 5' widths 16' and 6' widths 14'-17')
 Rack & gear jack with caster wheel
 Emergency breakaway system: switch, cable and battery box complete with battery (less charger)

Design Features & Hardware

Standard profile 12" radius corner galvanized roof
 All steel frame with formed galvanized side panels
 3' sides with 1" x 3" tubing above
 Rubber mounted optical window in front
 Two chrome circle vents in front
 Treated floor
 Greasable exterior hinges
 Chrome trim with colored vinyl insert
 Pin striping (upper and lower region only)
 Tag bracket

Load Area Equipment

1" square tubing center gate (no center gate on 10' and 12' trailers)
 Side access door on curb side (no side access door on 10' trailer)
 Full swing half sliding rear gate
 Four inside tie rings, No outside

Lights

DOT required lighting (stop, turn, tail, tag, marker, & clearance)